

SUB
#2

95. (Amended) The electronic inventory system of claim 94, wherein each passive RFID tag counts said clock signals and when the count is equivalent to said first permanent identification number, transmits its reply to said tag reader.

96. (Amended) The electronic inventory system of claim 95, wherein said tag reader accumulates said replies of each tag that responded.

97. (Amended) The electronic inventory system of claim 96, wherein said tag reader polls all tags whose reply conflicted with another tag.

3

98. (Amended) The electronic inventory of claim 92, wherein said first and second permanent identification numbers are a tag identification number (Tag ID) and a manufacturer number, wherein said signal is a clock signal, wherein each tag further comprises:

means for receiving a wake-up signal followed by a first clock signal;

means for incrementing a first tag count in response to said first clock signal;

means for transmitting said Tag ID assigned to said tag when said Tag ID corresponds to said first tag count;

means for receiving a second clock signal;

means for incrementing a second tag count in response to said second clock signal; and

means for transmitting said manufacturer number assigned to said tag when said manufacturer number of said tag corresponds to said second count.

99. (Amended) The electronic inventory of claim 92, wherein said first and second permanent identification numbers are a tag identification number (Tag ID) and a manufacturer number, wherein said signal is a clock signal, wherein said tag reader comprises:

means for transmitting a wake-up signal followed by a first clock signal;

means for incrementing a first reader count in response to said first clock signal,

means for receiving a Tag ID transmitted by a tag in response to said first clock signal;

means for storing a given first reader count when more than one tag responds to said first clock signal that corresponds to said given first reader count;

means for transmitting said given first reader count followed by a second clock signal; and

means for receiving a manufacturer number transmitted by a tag in response to said second clock signal.

101. (Amended) An automated, real-time electronic inventory system, comprising:

- (A) a plurality of passive radio frequency identification (RFID) tags, wherein each tag is assigned a plurality of identification numbers, wherein said RFID tags are configured to receive and transmit signals; and
- (B) a tag reader having means for transmitting a signal to said passive RFID tags and means for resolving contention resolution between multiple RFID tags that respond to said signal;
- (C) wherein said RFID tags are configured to receive a signal from said reader, evaluate one or more of said plurality of identification numbers, and reply to said signal if appropriate.

106. (Amended) A system for locating a tag, wherein each tag is assigned a first permanent identification number and a second permanent identification number, the system comprising:

a tag reader configured to transmit a first value corresponding to the first permanent identification number of a tag to be located and a second value corresponding to the second permanent identification number of a tag to be located ; and

a tag that transmits, in response to receiving said first value, the first permanent identification number assigned to said tag when the first permanent identification number assigned to said tag corresponds to said first value, wherein said tag further transmits, in response to receiving said second value, the second permanent identification number

assigned to said tag when the second permanent identification number assigned to said tag corresponds to said second value.

107. (Amended) A radio frequency identification tag, wherein each tag is assigned a first permanent identification number and a second permanent identification number, wherein the tag is interrogated by a tag reader having means for transmitting a first clock signal and for incrementing a first reader count in response to the first clock signal, means for storing the first reader count when more than one tag responds to the first clock signal that corresponds to the first reader count, and means for transmitting the stored first reader count followed by a second clock signal, the tag comprising:

means for incrementing a first tag count in response to the first clock signal, and means for transmitting the first permanent identification number assigned to the tag when the permanent identification number of the tag corresponds to said first tag count,

means for incrementing a second tag count in response to receiving the at least one second clock signal, and

means for transmitting the second permanent identification number assigned to the tag when the second permanent identification number of the tag corresponds to said second tag count.

108. (Amended) A method for conducting an inventory of tags, wherein each tag is assigned a first permanent identification number and a second permanent identification number, the method comprising the steps of:

at a tag reader, transmitting a first clock signal, waiting for a reply from a plurality of the tags, and transmitting a first reader count followed by a second clock signal; and

at each tag,

incrementing a first tag count in response to said first clock signal and

transmitting the first permanent identification number assigned to said tag when the first permanent identification number of said tag corresponds to said first tag count;

06 F41
Cmnd

at each tag that responds to said transmitted first reader count, incrementing a second tag count in response to said second clock signal, and transmitting the second permanent identification number assigned to said tag when the second permanent identification number of said tag corresponds to said second count.

Please add the following claim:

SUB
E5

109. (New) A method for conducting an electronic inventory of radio frequency identification tags, the method comprising the steps of:

- Q7
- (A) transmitting a first signal to a plurality of passive radio frequency identification (RFID) tags, wherein each tag is assigned a first identification number and a second identification number, wherein said RFID tags are configured to receive and transmit signals; and
 - (B) receiving a reply from said plurality of passive RFID tags, said tags responding to said first signal based on the value of said first identification number;
 - (C) resolving contention between multiple RFID tags if there is a conflict between at least two of said RFID tags subsequent to said RFID tags responding to said first signal, including transmitting a second signal to said plurality of passive RFID tags.

110. (New) The method of claim 109, wherein at least one of said RFID tags includes a sensor, the method further including receiving sensor data from at least one RFID tag.

111. (New) The method of claim 109, further comprising receiving a reply to said second signal from at least one RFID tag based on the value of said second identification number.

Sub
E6

7

112. (New) The electronic inventory system of claim 92, wherein at least one of said plurality of passive RFID tags are manufactured on a flexible substrate.
113. (New) The electronic inventory system of claim 101, wherein at least one of said plurality of passive RFID tags are manufactured on a flexible substrate.
114. (New) The system of claim 106, wherein said tag includes a sensor.
115. (New) The system of claim 106, wherein said tag is manufactured on a flexible substrate.
116. (New) The tag of claim 107, wherein the tag further includes a sensor.
117. (New) The tag of claim 107, wherein the tag is manufactured on a flexible substrate.

078

Please cancel claims 76-91, 100, and 105 without prejudice or disclaimer.